

-GENESIS-

General Purpose Security & Control Cable Part Number: 1204

22 AWG 4 Stranded Conductors Shielded

Ratings CM, CL2, Sunlight Resistant
Approvals ETL Listed

Construction

Conductor 22 AWG 7 Strand Bare Copper
Conductor Count 4
Insulation Polypropylene (0.006" nom.)
Insulation Colors Black, Red, White, Green
Lay Length 2.5" nom.
Shielding Aluminum Foil/Mylar w/ 24 AWG Tinned-Copper Drain
Rip Cord Yes
Jacket PVC (0.015 " nom.)
Overall Diameter 0.139" nom.
Print Legend GENESIS P/N 1204 4C22 SHIELDED 3038058 (ETL) CL2 OR CM C(ETL)US SUN RES
(RoHS) W/O #XXXXXX-XXXXXX XXXX FT DEVICE/ZONE A B C D E F 1 2 3 4 5 6 7 8 9

Properties

Operating Voltage 300 Volts max.
DC Resistance 16.9 Ohms/1000' at 20°C
Capacitance 28.2 pF/ft. nom.
Impedance 53 Ohms nom.

Temperature -20°C to 60°C
Flame Rating UL 1685 Vertical Tray
RoHS Compliant Yes

Country of Origin USA