

# -GENESIS-

## General Purpose Security & Control Cable Part Number: 1212

### 20 AWG 2 Stranded Conductors Shielded

**Ratings** CM, CL2, Sunlight Resistant  
**Approvals** ETL Listed

#### Construction

**Conductor** 20 AWG 7 Strand Bare Copper  
**Conductor Count** 2  
**Insulation** Polypropylene (0.006" nom.)  
**Insulation Colors** Black, Red  
**Lay Length** 2.25" nom.  
**Shielding** Aluminum Foil/Mylar w/ 24 AWG Tinned-Copper Drain  
**Rip Cord** Yes  
**Jacket** PVC (0.015 " nom.)  
**Overall Diameter** 0.138" nom.  
**Print Legend** GENESIS P/N 1212 2C20 SHIELDED 3038058 (ETL) CL2 OR CM C(ETL)US SUN RES  
(RoHS) W/O #XXXXXX-XXXXXX XXXX FT DEVICE/ZONE A B C D E F 1 2 3 4 5 6 7 8 9

#### Properties

**Operating Voltage** 300 Volts max.  
**DC Resistance** 10.5 Ohms/1000' at 20°C  
**Capacitance** 36.9 pF/ft. nom.  
**Impedance** 41 Ohms nom.

**Temperature** -20°C to 60°C  
**Flame Rating** UL 1685 Vertical Tray  
**RoHS Compliant** Yes

**Country of Origin** USA