

# -GENESIS-

## General Purpose Security & Control Cable Part Number: 1215

### 18 AWG 4 Stranded Conductors Shielded

**Ratings** CM, CL2, Sunlight Resistant

**Approvals** ETL Listed

#### Construction

**Conductor** 18 AWG 19 Strand Bare Copper

**Conductor Count** 4

**Insulation** Polypropylene (0.006" nom.)

**Insulation Colors** Black, Red, White, Green

**Lay Length** 3.5" nom.

**Shielding** Aluminum Foil/Mylar w/ 24 AWG Tinned-Copper Drain

**Rip Cord** Yes

**Jacket** PVC (0.015 " nom.)

**Overall Diameter** 0.178" nom.

**Print Legend** GENESIS P/N 1215 4C18 SHIELDED 3038058 (ETL) CL2 OR CM C(ETL)US SUN RES  
(RoHS) W/O #XXXXXX-XXXXXX XXXX FT DEVICE/ZONE A B C D E F 1 2 3 4 5 6 7 8 9

#### Properties

**Operating Voltage** 300 Volts max.

**DC Resistance** 6.66 Ohms/1000' at 20°C

**Capacitance** 36.3 pF/ft. nom.

**Impedance** 41 Ohms nom.

**Temperature** -20°C to 60°C

**Flame Rating** UL 1685 Vertical Tray

**RoHS Compliant** Yes

**Country of Origin** USA