

-GENESIS-

General Purpose Security & Control Cable Part Number: 1229

16 AWG 3 Stranded Conductors Shielded

Ratings CM, CL2, Sunlight Resistant
Approvals ETL Listed

Construction

Conductor 16 AWG 26 Strand Bare Copper
Conductor Count 3
Insulation Polypropylene (0.007" nom.)
Insulation Colors Black, Red, White
Lay Length 3" nom.
Shielding Aluminum Foil/Mylar w/ 24 AWG Tinned-Copper Drain
Rip Cord Yes
Jacket PVC (0.015 " nom.)
Overall Diameter 0.186" nom.
Print Legend GENESIS P/N 1229 3C16 SHIELDED 3038058 (ETL) CL2 OR CM C(ETL)US SUN RES
(RoHS) W/O #XXXXXX-XXXXXX XXXX FT DEVICE/ZONE A B C D E F 1 2 3 4 5 6 7 8 9

Properties

Operating Voltage 300 Volts max.
DC Resistance 4.19 Ohms/1000' at 20°C
Capacitance 37.3 pF/ft. nom.
Impedance 40 Ohms nom.

Temperature -20°C to 60°C
Flame Rating UL 1685 Vertical Tray
RoHS Compliant Yes

Country of Origin USA