

Description: 22 AWG 2Pr Str OAS CM-CL2
Specifications: UL Standards 13, & 444; NEC Article 725
Assembly: Tubed jacket over, twisted, cabled, overall shielded pairs

Construction:

Conductor 22 AWG 7/30 Bare Copper
Insulation Polypropylene
Insulation Thickness 0.006" nom.
Insulation Colors Pairs - Blk/Red, Blk/Wht
Insulation Diameter 0.042" nom.
Lay Length 1.5" nom.(pair), 3.0" nom.(cable)
Drain Wire 22 AWG 7/30 Tinned Copper
Shield .001" Thick Aluminum/Mylar

Jacket PVC
Jacket Thickness 0.015" nom.
Outside Diameter 0.181" nom.
Legend (Ink Print) HONEYWELL 22 AWG 2/PR (ETL) TYPE CM-CL2 - Sun. Res. (RoHS)- 3038058
W/O# XXXXXX-XXX XXXXX FT DEVICE/ZONE A B C D E F 1 2 3 4 5 6 7 8 9

Properties

Temperature Rating -20 to 60 °C
Operating Voltage 300 Volts max.
Capacitance 30 pf/ft nom.
Impedance 50 Ohms nom.
DC Resistance 16.5 Ohms/M' at 20°C
Flame Rating UL Vertical Tray