

Description: 22 AWG 3Pr Str OAS CM-CL2  
Specifications: UL Standards 13, & 444; NEC Article 725  
Assembly: Tubed jacket over, twisted, cabled, overall shielded pairs

#### Construction:

Conductor: 22 AWG 7/30 Bare Copper  
Insulation: Polypropylene  
Insulation Thickness: 0.006" nom.  
Insulation Colors: Pairs - Blk/Red, Blk/Wht, Blk/Grn  
Insulation Diameter: 0.042" nom.  
Lay Length: 1.5" nom.(pair), 3.25" nom.(cable)  
Drain Wire: 22 AWG 7/30 Tinned Copper  
Shield: .001" Thick Aluminum/Mylar

Jacket: PVC  
Jacket Thickness: 0.015" nom.  
Outside Diameter: 0.197" nom.  
Legend (Ink Print): HONEYWELL 22 AWG 3/PR (ETL) TYPE CM-CL2 - Sun. Res. (RoHS)- 3038058  
W/O# XXXXXX-XXX XXXXX FT DEVICE/ZONE A B C D E F 1 2 3 4 5 6 7 8 9

#### Properties

Temperature Rating: -20 to 60 °C  
Operating Voltage: 300 Volts max.  
Capacitance: 30 pf/ft nom.  
Impedance: 50 Ohms nom.  
DC Resistance: 16.5 Ohms/M' at 20°C  
Flame Rating: UL Vertical Tray