



GENESIS SERIES CABLE

**Low Voltage Cable
Part No. 2221**

Description: 16 AWG 2/C Stranded OAS CMR-CL2R-FT4
Specifications: UL Standards 13, & 444; NEC Article 725

Construction:

Conductor 16 26/30 Bare Copper
Insulation Polypropylene
Insulation Thickness 0.006" nom.
Insulation Colors Blk,Red
Insulation Diameter 0.070" nom.
Lay Length (Twist) 2.75" nom.
Drain Wire 20 7/28 Tinned-Copper
Shield Alum/Mylar tape

Jacket PVC
Jacket Thickness 0.015" nom.
Outside Diameter 0.176" nom.
Legend (Ink Print)

HONEYWELL 16 AWG 2/C (ETL) TYPE CMR-CL2R 3038058 (RoHS) W/O# XXXXXX-XXX C(ETL) FT4 XXXXX FT
DEVICE/ZONE A B C D E F 1 2 3 4 5 6 7 8 9

Properties

Temperature Rating -20 to 60 °C
Operating Voltage 300 Volts max.
Capacitance 40 pf/ft nom.
Impedance 40 Ohms nom.
DC Resistance 4.15 Ohms/M' at 20°C
Flame Rating UL 1666 - Riser