

-GENESIS-

General Purpose Power Limited Fire Alarm Cable Part Number: 4206

16 AWG 2 Solid Conductors Shielded

Ratings FPL, CL2, Sunlight Resistant
Approvals UL Listed

Construction

Conductor 16 AWG Solid Bare Copper
Conductor Count 2
Insulation Polypropylene (0.008" nom.)
Insulation Colors Black, Red
Lay Length 3" nom.
Shielding Aluminum Foil/Mylar w/ 24 AWG Tinned-Copper Drain
Rip Cord Yes
Jacket PVC (0.016 " nom.)
Overall Diameter 0.177" nom.
Print Legend GENESIS P/N 4206 2C16 SHIELDED E175105 (UL) FPL OR CL2 SUN RES (RoHS) 75C W/O
#XXXXXX-XXXXXX XXXX FT DEVICE/ZONE A B C D E F 1 2 3 4 5 6 7 8 9

Properties

Operating Voltage 300 Volts max.
DC Resistance 4.1 Ohms/1000' at 20°C
Capacitance 41.7 pF/ft. nom.
Impedance 37 Ohms nom.

Temperature -20°C to 75°C
Flame Rating UL 1685 Vertical Tray
RoHS Compliant Yes

Country of Origin USA