

## RTT750HR.NX900



**Article Number:** 115-00001

**Releasable Cable Tie, 29.6" Long, 200 lb Tensile Strength, PA66, Yellow, 5/pkg**



### Base Data

**Local Order Number** RTT750HR.NX900

**Type** RTT750HR

**Color** Yellow (YE)  
Red (RD)

**Features and Benefits**

- The heavy duty Speedy tie features a specially designed head and patented trigger to allow for repeated use in temporary bundling applications.
- Additional design feature on the head allows excess strap to be tucked away after installation.

**Product Description** HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes or temporary bundling are necessary. The head design guarantees high tensile strength even after repeated use.

**Fixation Method (FF)** None

**Identification Plate Position** none

**Releasable Closure (Yes/No)** Yes

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Short Description** Releasable Cable Tie, 29.6" Long, 200 lb Tensile Strength, PA66, Yellow, 5/pkg

### Product Dimensions

**Minimum Tensile Strength (imperial)** 200.0 lbs

**Minimum Tensile Strength (N)** 888.0 N

**Length L (imperial)** 29.6 "

**Length L (metric)** 752.0 mm

**Width W (imperial)** 0.51 "

**Width W (metric)** 13.0 mm

**Bundle Diameter min (imperial)** 1.6 "

**Bundle Diameter min (metric)** 40.0 mm

**Bundle Diameter max (imperial)** 8.3 "

**Bundle Diameter max (metric)** 210 mm

**Thickness T (imperial)** 0.075 "

**Thickness T (Metric)** 1.9 mm

### Logistics and Packaging

**Quantity per** bag

**Package Quantity** 5

**Carton Quantity** 60 Pieces

**Weight (Metric)** 23.2 kg

## Material and Specifications

---

<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL94 V2
<b>Operating Temperature</b>	-40 °F to +185 °F (-40 °C to +85 °C)
<b>ROHS Conformity</b>	Yes